

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
 Product name : Lexel White Lower VOC

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Caulking

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the OSHA requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, SDS or both in accordance with applicable government regulations

1.4. Supplier's details

Supplier

Sashco Inc.
 14802 Grant St.
 Thornton, CO, 80023
 USA
 T 800-767-5656
info@sashco.com

1.5. Emergency phone number

Emergency number : 800-535-5053

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2
 Carcinogenicity, Category 2

Highly flammable liquid and vapor.
 Suspected of causing cancer.

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Highly flammable liquid and vapor
 Suspected of causing cancer.

Precautionary statements (GHS US)

: Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Keep container tightly closed.
 Ground/Bond container and receiving equipment.

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Use explosion-proof equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Wear protective gloves, protective clothing, eye protection, face protectionIf exposed or concerned: Get medical advice/attention.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
In case of fire: Use Water fog. Dry chemical. Carbon dioxide. Foam. to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)
Para-Chlorobenzotrifluoride	CAS-No.: 98-56-6	30 - 60
Titanium Dioxide	CAS-No.: 13463-67-7	1 – 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash clothing before re-using. Get medical attention if irritation develops and persists.
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : May cause drowsiness or dizziness. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure may cause skin dryness or cracking.

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water fog. Dry chemical. Carbon dioxide. Foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Products of combustion may include, and are not limited to: oxides of carbon.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray or fog for cooling exposed containers.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.
------------------	---

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions	: Prevent entry to sewers and public waters.
---------------------------	--

6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak if safe to do so. Remove ignition sources. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Do not breathe gas, fumes, vapour or spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Always wash hands after handling the product.
Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep out of the reach of children. Keep container tightly closed in a cool, well-ventilated place. Protect from moisture. Keep container tightly closed. Store locked up.
Incompatible materials	: Refer to Section 10 on Incompatible Materials.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Titanium Dioxide (13463-67-7)	
USA - ACGIH® - Threshold Limit Values	
Local name	Titanium dioxide
ACGIH® TLV® TWA	0.2 mg/m³ (nanoscale respirable particulate matter) 2.5 mg/m³ (finescale respirable particulate matter)
Remark (ACGIH®)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH® chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m³ (total dust)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	5000 mg/m³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	2.4 mg/m³ (CIB 63-fine) 0.3 mg/m³ (CIB 63-ultrafine, including engineered nanoscale)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide readily accessible eye wash stations and safety showers. Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Color	: White
Odor	: Solvent
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 35 °C / 95 °F
Flash point	: 58 °F / 14.4 °F [ASTM D-93]
Flammability (solid, gas)	: Highly flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.08
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 330 000 cP at 25°C / 77°F
Explosion limits	: No data available
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials. Direct sunlight.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Para-Chlorobenzotrifluoride (98-56-6)

LD50 oral rat	13 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 3300 mg/kg body weight Animal: rabbit
LC50 inhalation rat	> 32.03 mg/l air Animal: rat, Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg (Source: IUCLID)
LC50 inhalation rat	5.09 mg/l/4h

Skin corrosion/irritation : Not classified

Titanium Dioxide (13463-67-7)

pH	7
----	---

Serious eye damage/irritation : Not classified

Titanium Dioxide (13463-67-7)

pH	7
----	---

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Para-Chlorobenzotrifluoride (98-56-6)

IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Titanium Dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Para-Chlorobenzotrifluoride (98-56-6)	
LOAEL (oral, rat, 90 days)	150 mg/kg body weight Animal: rat
NOAEL (oral, rat, 90 days)	40 mg/kg body weight Animal: rat, Animal sex: male
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause drowsiness or dizziness. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Para-Chlorobenzotrifluoride (98-56-6)	
LC50 - Fish [1]	3 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	3.68 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 0.41 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other: Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

12.2. Persistence and degradability

Lexel White Lower VOC	
Persistence and degradability	Not established.
Para-Chlorobenzotrifluoride (98-56-6)	
Persistence and degradability	Rapidly degradable
Titanium Dioxide (13463-67-7)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Lexel White Lower VOC	
Bioaccumulative potential	Not established.
Para-Chlorobenzotrifluoride (98-56-6)	
Partition coefficient n-octanol/water	3.7 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapors are flammable.

SECTION 14 Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

UN-No. (DOT)	: UN1993
UN-No. (IMDG)	: 1993
UN-No. (IATA)	: 1993

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (Para-Chlorobenzotrifluoride and Naphtha (petroleum), hydrotreated light)
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S. (Para-Chlorobenzotrifluoride and Naphtha (petroleum), hydrotreated light)
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s. (Para-Chlorobenzotrifluoride and Naphtha (petroleum), hydrotreated light)
Limited Quantity Notes (DOT)	: Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (limited quantity)

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Limited Quantity Notes (IMDG)	: Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.
Proper Shipping Name (IMDG)	: Flammable liquids, n.o.s. (limited quantity)
Limited Quantity Notes (IATA)	: Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.
Proper Shipping Name (IATA)	: Flammable liquids, n.o.s. (limited quantity)


14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT)	: 3
Hazard labels (DOT)	: 3



Class (DOT)	: Limited quantity
Hazard labels (DOT) LTD QTY - Limited quantity	:




IMDG

Transport hazard class(es) (IMDG)	: 3
Hazard labels (IMDG)	: 3



Class (IMDG)	: Limited quantity
Hazard labels (IMDG) LTD QTY - Limited quantity	:



IATA

Transport hazard class(es) (IATA)	: 3
Hazard labels (IATA)	: 3



Class (IATA)	: Limited quantity
Hazard labels (IATA) LTD QTY - Limited quantity	:



Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

14.4. Packing group

Packing group (DOT)	: II Not applicable if Limited Quantity applies
Packing group (IMDG)	: II Not applicable if Limited Quantity applies
Packing group (IATA)	: II Not applicable if Limited Quantity applies

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions	: Do not handle until all safety precautions have been read and understood.
-------------------------------	---

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. State regulations

**WARNING:**

This product can expose you to chemicals including p-Chloro- α,α,α -trifluorotoluene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SECTION 16 Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Issue date	: 4/6/2026
Other information	: None.
Prepared by	: Nexreg Compliance Inc. www.Nexreg.com



NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating	
Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Health	: * - Chronic (long-term) health effects may result from repeated overexposure

Lexel White Lower VOC

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024

Flammability	: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB IC)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: B - Safety glasses, Gloves

Indication of changes:
None

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.